Page 2 Dkr: 279 209US2

Filing Date: December 18, 2001 SYSTEM AND METHOD FOR DETECTION ENHANCEMENT PROGRAMMING

## IN THE CLAIMS

Please amend the claims as follows.

## 1-13. (Canceled)

(Currently Amended) A programmer for a user to program a pulse generator to detect a clinical rhythm and selectively apply therapy for the detected clinical rhythm, comprising:

a first module for receiving a user-provided selection of a clinical rhythm, wherein the clinical rhythm is associated with two or more available detection enhancements that are made available based on the selected clinical rhythm for selection by the user to add specificity for determining when to deliver shock therapy for the selected clinical rhythm, wherein:

> the available detection enhancements are sets of rules for determining when to deliver shock therapy for the selected clinical rhythm; and the first module is preprogrammed to provide a selection of at least one detection enhancement from the two or more available detection enhancements that are associated with the clinical rhythm; and

a second module for receiving a user-provided selection to modify the selection of the at least one detection enhancement provided by the preprogrammed first module to at least one other detection enhancement from the two or more available detection enhancements that are associated with the clinical rhythm.

- 15. (Previously Presented) The programmer of claim 14, wherein the at least one detection enhancement has at least one parameter, the first module is preprogrammed to provide a setting for the at least one parameter for the at least one detection enhancement, and the second module is used to receive a user-provided selection to modify the setting for the at least one parameter.
- 16. (Previously Presented) The programmer of claim 14, further comprising a communication module for communicating with a pulse generator to program the pulse generator with the at least one detection enhancement.

Filing Date: December 18, 2001

Title: SYSTEM AND METHOD FOR DETECTION ENHANCEMENT PROGRAMMING

Page 3 Dkt: 279.209US2

17. (Previously Presented) The programmer of claim 14, further comprising a programmer screen, wherein the second module provides a number of screen displays on the programmer screen, and the number of screen displays are layered such that a first screen provides a capability to activate the at least one detection enhancement which is seeded with at least one parameter, and a second screen provides a capability to change the at least one parameter for the at least one detection enhancement.

## 18. (Currently Amended) A programmer, comprising:

a selection module for receiving a selection of a clinical rhythm from a user, wherein the clinical rhythm is associated with at least two available detection enhancements wherein the available detection enhancements are sets of rules to determine when to deliver shock therapy and each detection enhancement includes at least one parameter that include at least one parameter; the at least two available detection enhancements being made available based on the selected clinical rhythm for selection by the user to add specificity for determining when to deliver shock therapy for the selected clinical rhythm, wherein the selection module includes artificial intelligence adapted to select a detection enhancement from the at least one parameter for the selected detection enhancement, and provide a setting for the at least one parameter for the selected detection enhancement, the selection module being adapted to receive a user provided selection of at least one other detection enhancement from the at least-two available detection enhancements in place of the detection enhancement selected by artificial intelligence;

a parameter modification module for receiving a user input to change the setting for the at least one parameter of the selected detected enhancement; and

a communication module for communicating with a pulse generator to program the pulse generator with the selected clinical rhythm and the associated at least one detection enhancement.

19. (Previously Presented) The programmer of claim 18, wherein the selection module provides a capability to select a number of tachyarrhythmia zones that are associated with the at least one parameter.

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 - EXPEDITED PROCEDURE

Serial Number: 10/025,958

Filing Date: December 18, 2001

SYSTEM AND METHOD FOR DETECTION ENHANCEMENT PROGRAMMING

Page 4 Dkr: 279 209US2

20. (Previously Presented) The programmer of claim 19, wherein the parameter modification module provides the capability to change detection parameters for the number of

tachvarrhythmia zones.

21. (Previously Presented) The programmer of claim 19, wherein the parameter modification

module provides the capability to change therapy parameters for the number of tachyarrhythmia

zones.

22. (Previously Presented) The programmer of claim 18, wherein the parameter modification

module provides at least one indicator for indicating whether a changed parameter has been

programmed in the pulse generator.

23. (Previously Presented) The programmer of claim 18, wherein the artificial intelligence

tracks parameter interaction among the set parameters and the changed parameters, and provides

at least one warning indicator for at least one parameter interaction.

24. (Currently Amended) The programmer of claim 18, wherein the at least one detection

enhancements include enhancement includes a V Rate > A Rate enhancement for delivering

therapy when a detected ventricular rate is determined to be greater than a detected atrial rate.

25. (Currently Amended) The programmer of claim 18, wherein the at least one detection

enhancements include enhancement includes an AFib Rate Threshold enhancement for inhibiting

ventricular therapy when a detected atrial rhythm is determined to be faster than a threshold.

26. (Currently Amended) The programmer of claim 18, wherein the at least one detection

enhancements include enhancement includes a Stability enhancement for inhibiting ventricular

therapy when a detected atrial rhythm is determined to be unstable.

Page 5 Dkt: 279.209US2

Serial Number: 10/025,958 Filing Date: December 18, 2001

Title: SYSTEM AND METHOD FOR DETECTION ENHANCEMENT PROGRAMMING

27. (Currently Amended) The programmer of claim 18, wherein the at-least-one detection enhancements include enhancement includes an Onset enhancement for inhibiting a therapy when a detected cardiac rate is determined to increase gradually.

- 28. (Currently Amended) The programmer of claim 18, wherein the at-least-one detection enhancements include enhancement includes a Shock If Unstable enhancement when a ventricular rhythm is determined to be unstable.
- 29. (Currently Amended) The programmer of claim 18, wherein the at least one detection enhancements include enhancement includes a Sustained Rate Duration (SRD) enhancement for overriding an inhibit therapy enhancement when a detected rate continues throughout a programmed time period.
- 30. (Previously Presented) The programmer of claim 18, wherein the at least one parameter includes at least one cardiac rhythm parameter that indicates when the at least one detection enhancement for the selected clinical rhythm applies.
- 31. (Currently Amended) A programmer for a user to program a pulse generator to detect a clinical rhythm and apply therapy for the detected clinical rhythm, comprising:

a communications module for communicating with the pulse generator;

control logic for programming the pulse generator using the communications module, wherein the control logic is adapted to program the pulse generator to detect and provide therapy for at least one clinical rhythm where the clinical rhythm is associated with two-or-more available detection enhancements, to program the pulse generator with at least one selected detection enhancement from the available detection enhancements associated with the at least one clinical rhythm, and to program the pulse generator with at least one parameter for the at least one selected detection enhancement; and

a display connected to the control logic to provide a number of screen displays used by the user to select the at least one clinical rhythm and modify the selection of the at least one detection enhancement from at least one preprogrammed detection enhancement to at least one Title: SYSTEM AND METHOD FOR DETECTION ENHANCEMENT PROGRAMMING

other detection enhancement from the available detection enhancements associated with the at least one clinical rhythm.

- 32. (Currently Amended) The programmer of claim 31, wherein the at least one <u>selected</u> detection enhancement is automatically seeded with a value for the at least one parameter, and the number of screen displays are used by the user to change the value for the at least one parameter.
- 33. (Previously Presented) The programmer of claim 32, wherein the number of screen displays are layered such a first screen display provides a the user with the ability to select the at least one detection enhancement, and a second screen provides the user with the ability to change the value for the at least one parameter.
- 34. (Previously Presented) The programmer of claim 33, wherein the first screen includes a number of tachyarrhythmia zones, and the number of tachyarrhythmia zones ranges between one and three zones as determined by a user input.
- 35. (Previously Presented) The programmer of claim 34, wherein each of the number of tachyarrhythmia zones includes a detection button, and selecting the detection button displays the second screen used to change detection parameters for at least one of the number of tachyarrhythmia zones.
- 36. (Previously Presented) The programmer of claim 34, wherein each of the number of tachyarrhythmia zones includes a therapy button, and selecting the therapy button displays the second screen used to change therapy parameters for the number of tachyarrhythmia zones.
- 37. (Previously Presented) The programmer of claim 33, wherein the first screen displays detection enhancement rhythm discrimination categories.

SYSTEM AND METHOD FOR DETECTION ENHANCEMENT PROGRAMMING

- 38. (Previously Presented) The programmer of claim 33, wherein the first screen provides an ECG display.
- The programmer of claim 31, wherein the at least one detection (Currently Amended) enhancement includes detection enhancements include at least one inhibit therapy enhancement for inhibiting the therapy for the at least one clinical rhythm.
- 40. (Currently Amended) The programmer of claim 39, wherein the at least one detection enhancement includes detection enhancements include at least one override enhancement for overriding the inhibit therapy enhancement.
- 41. (Previously Presented) The programmer of claim 40, wherein the at least one inhibit therapy enhancement includes an AFib Rate Threshold enhancement for inhibiting ventricular therapy when a detected atrial rhythm is faster than a threshold.
- 42. (Previously Presented) The programmer of claim 40, wherein the at least one inhibit therapy enhancement includes a Stability enhancement for inhibiting ventricular therapy when a detected atrial rhythm is determined to be unstable.
- 43. (Previously Presented) The programmer of claim 40, wherein the at least one inhibit therapy enhancement includes an Onset enhancement for inhibiting a therapy when a detected rate increases gradually.
- 44. (Previously Presented) The programmer of claim 40, wherein the at least one override inhibit enhancement includes a V Rate > A Rate enhancement for delivering therapy when a detected ventricular rate is greater than a detected atrial rate.
- 45. (Previously Presented) The programmer of claim 40, wherein the at least one override inhibit enhancement includes a Shock if Unstable enhancement when a ventricular rhythm is determined to be unstable.

Filing Date: December 18, 2001

Title: SYSTEM AND METHOD FOR DETECTION ENHANCEMENT PROGRAMMING

46. (Previously Presented) The programmer of claim 40, wherein the at least one override inhibit enhancement includes a Sustained Rate Duration (SRD) enhancement for overriding an inhibit therapy enhancement when a detected rate continues throughout a programmed time period.